

m o o o i

Random Light II

BERTJAN POT




Random Light II transmits a feeling of simplicity, lightness and a touch of magic in a contemporary style. Due to how they're made, each Random Light is unique. They're never completely round, yet always beautifully transparent and delicate.

Detailing



The open and random texture of the Random Light plays with shadow while it emits a soft glow.

Colours




Black

White

Random Light II / large

Dimensions

Ø105cm | 41.3"



Product

WIDTH 105cm | 41.3"
HEIGHT 105cm | 41.3"
DEPTH 105cm | 41.3"
DIAMETER 105cm | 41.3"
WEIGHT NETTO 2.5kg | 5.51lbs

Packaging

WIDTH 110cm | 43.3"
HEIGHT 110cm | 43.3"
CUBAGE 1.33m³ | 47ft³
LENGTH 110cm | 43.3"
WEIGHT 13.5kg | 29.76lbs

Technical CCC

MATERIAL

Sphere from fiberglass with epoxy resin, chromed steel pendant

ENERGY LABEL

A++ to E

LIGHTSOURCE TYPE

Incandescent

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

1

DIAMETER SHADE

105cm | 41.3"

INPUT VOLTAGE

220-240V

FREQUENCY

50/60

MAX POWER CONSUMPTION

60W

LAMPHOLDER

E27

RECOMMENDED LIGHTSOURCE

60W MAX type G, 10W LED light included

LIFETIME

50000 hours

CABLE COLOUR

Black

CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

CANOPY

Pebble II Black, ABS, Pebble II White, ABS

CRI

90

LIGHT DIRECTION

All directions

LIGHT OUTPUT

800 lm

DIMMING & LIGHTING CONTROL

Mains dimmable with compatible light source

See last page for more information about the dimming possibilities.



Technical CE

MATERIAL

Sphere from fiberglass with epoxy resin, chromed steel pendant

ENERGY LABEL

A++ to E

LIGHTSOURCE TYPE

Incandescent

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

1

DIAMETER SHADE

105cm | 41.3"

INPUT VOLTAGE

220-240V

FREQUENCY

50/60

MAX POWER CONSUMPTION

60W

LAMPHOLDER

E27

RECOMMENDED LIGHTSOURCE

60W MAX type G, 10W LED light included

LIFETIME

50000 hours

CABLE COLOUR

Black

CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

CANOPY

Pebble II Black, ABS, Pebble II White, ABS

CRI

90

LIGHT DIRECTION

All directions

LIGHT OUTPUT

800 lm

DIMMING & LIGHTING CONTROL

Mains dimmable with compatible light source

See last page for more information about the dimming possibilities.



Technical UL

MATERIAL

Sphere from fiberglass with epoxy resin, chromed steel pendant

ENERGY LABEL

A++ to E

LIGHTSOURCE TYPE

Incandescent

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

1

DIAMETER SHADE

105cm | 41.3"

INPUT VOLTAGE

110-130V

FREQUENCY

50/60

MAX POWER CONSUMPTION

60W

LAMPHOLDER

E26

RECOMMENDED LIGHTSOURCE

60W MAX type G, 10W LED light included

LIFETIME

50000 hours

CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

CRI

90

LIGHT OUTPUT

800 lm

CABLE COLOUR

Black

CANOPY

Pebble II Black, ABS, Pebble II White, ABS

LIGHT DIRECTION

All directions

DIMMING & LIGHTING CONTROL

Mains dimmable with compatible light source

See last page for more information about the dimming possibilities.

Random Light II / medium

Dimensions

Ø80cm | 31.5"



Product

WIDTH 80cm | 31.5"**HEIGHT** 80cm | 31.5"**DEPTH** 80cm | 31.5"**DIAMETER** 80cm | 31.5"**WEIGHT NETTO** 1.8kg | 3.97lbs

Packaging

WIDTH 87cm | 34.3"**HEIGHT** 87cm | 34.3"**CUBAGE** 0.66m³ | 23.25ft³**LENGTH** 87cm | 34.3"**WEIGHT** 5.5kg | 12.13lbs

Technical CCC

MATERIAL

Sphere from fiberglass with epoxy resin, chromed steel pendant

ENERGY LABEL

A++ to E

LIGHTSOURCE TYPE

Incandescent

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

1

DIAMETER SHADE

80cm | 31.5"

INPUT VOLTAGE

220-240V

FREQUENCY

50/60

MAX POWER CONSUMPTION

60W

LAMPHOLDER

E27

RECOMMENDED LIGHTSOURCE

60W MAX type G, 10W LED light included

LIFETIME

50000 hours

CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

CRI

90

LIGHT OUTPUT

800 lm

CABLE COLOUR

Black

CANOPY

Pebble II Black, ABS, Pebble II White, ABS

LIGHT DIRECTION

All directions

DIMMING & LIGHTING CONTROL

Mains dimmable with compatible light source

See last page for more information about the dimming possibilities.

*Technical CE***MATERIAL**

Sphere from fiberglass with epoxy resin, chromed steel pendant

ENERGY LABEL

A++ to E

LIGHTSOURCE TYPE

Incandescent

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

1

DIAMETER SHADE

80cm | 31.5"

INPUT VOLTAGE

220-240V

FREQUENCY

50/60

MAX POWER CONSUMPTION

60W

LAMPHOLDER

E27

RECOMMENDED LIGHTSOURCE

60W MAX type G, 10W LED light included

LIFETIME

50000 hours

CABLE COLOUR

Black

CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

CANOPY

Pebble II Black, ABS, Pebble II White, ABS

CRI

90

LIGHT DIRECTION

All directions

LIGHT OUTPUT

800 lm

DIMMING & LIGHTING CONTROL

Mains dimmable with compatible light source

See last page for more information about the dimming possibilities.

*Technical UL***MATERIAL**

Sphere from fiberglass with epoxy resin, chromed steel pendant

ENERGY LABEL

A++ to E

LIGHTSOURCE INCLUDED

Yes

DIAMETER SHADE

80cm | 31.5"

FREQUENCY

50/60

LAMPHOLDER

E26

LIFETIME

50000 hours

CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

CRI

90

LIGHT OUTPUT

800 lm

LIGHTSOURCE TYPE

Incandescent

NUMBER OF LIGHTSOURCES

1

INPUT VOLTAGE

110-130V

MAX POWER CONSUMPTION

60W

RECOMMENDED LIGHTSOURCE

60W MAX type G, 10W LED light included

CABLE COLOUR

Black

CANOPY

Pebble II Black, ABS, Pebble II White, ABS

LIGHT DIRECTION

All directions

DIMMING & LIGHTING CONTROL


Mains dimmable with compatible light source

See last page for more information about the dimming possibilities.

Random Light II / small

Dimensions

Ø50cm | 19.7"



Product

WIDTH 50cm | 19.7"

HEIGHT 50cm | 19.7"

DEPTH 50cm | 19.7"

DIAMETER 50cm | 19.7"

WEIGHT NETTO 1.2kg | 2.65lbs

Packaging

WIDTH 51cm | 20.1"

HEIGHT 53cm | 20.9"

CUBAGE 0.14m³ | 4.87ft³

LENGTH 51cm | 20.1"

WEIGHT 2.5kg | 5.51lbs

Technical CCC

MATERIAL

Sphere from fiberglass with epoxy resin, chromed steel pendant

ENERGY LABEL

A++ to E

LIGHTSOURCE INCLUDED

Yes

DIAMETER SHADE

50cm | 19.7"

FREQUENCY

50/60

LAMPHOLDER

E27

LIFETIME

50000 hours

CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

CRI

90

LIGHT OUTPUT

800 lm

LIGHTSOURCE TYPE

Incandescent

NUMBER OF LIGHTSOURCES

1

INPUT VOLTAGE

220-240V

MAX POWER CONSUMPTION

60W

RECOMMENDED LIGHTSOURCE

60W MAX type G, 10W LED light included

CABLE COLOUR

Black

CANOPY

Pebble II Black, ABS, Pebble II White, ABS

LIGHT DIRECTION

All directions

DIMMING & LIGHTING CONTROL

Mains dimmable with compatible light source

See last page for more information about the dimming possibilities.*Technical CE***MATERIAL**

Sphere from fiberglass with epoxy resin, chromed steel pendant

ENERGY LABEL

A++ to E

LIGHTSOURCE INCLUDED

Yes

DIAMETER SHADE

50cm | 19.7"

FREQUENCY

50/60

LAMPHOLDER

E27

LIFETIME

50000 hours

CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

LIGHTSOURCE TYPE

Incandescent

NUMBER OF LIGHTSOURCES

1

INPUT VOLTAGE

220-240V

MAX POWER CONSUMPTION

60W

RECOMMENDED LIGHTSOURCE

60W MAX type G, 10W LED light included

CABLE COLOUR

Black

CANOPY

Pebble II Black, ABS, Pebble II White, ABS

CRI

90

LIGHT OUTPUT

800 lm

LIGHT DIRECTION

All directions

DIMMING & LIGHTING CONTROL

Mains dimmable with compatible light source

See last page for more information about the dimming possibilities.*Technical UL***MATERIAL**

Sphere from fiberglass with epoxy resin, chromed steel pendant

ENERGY LABEL

A++ to E

LIGHTSOURCE TYPE

Incandescent

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

1

DIAMETER SHADE

50cm | 19.7"

INPUT VOLTAGE

110-130V

FREQUENCY

50/60

MAX POWER CONSUMPTION

60W

LAMPHOLDER

E26

RECOMMENDED LIGHTSOURCE

60W MAX type G, 10W LED light included

LIFETIME

50000 hours

CABLE COLOUR

Black

CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

CANOPY

Pebble II Black, ABS, Pebble II White, ABS

CRI

90

LIGHT DIRECTION

All directions

LIGHT OUTPUT

800 lm

DIMMING & LIGHTING CONTROL

Mains dimmable with compatible light source

See last page for more information about the dimming possibilities.

Dimming & Lighting Control

Mains dimmable with compatible light source

Compatible models: large CE, large UL, medium CE, medium UL, small CE, small UL
